


RIVETTI A STRAPPO IN INOX A2



Rivetti a strappo in acciaio inox A2

- A norma DIN 7337
- Occhiello e chiodo in acciaio inox A2



Ø	Lunghezza	Dk	Ø Foro	Serraggio Min-Max	Art.
3	6	6,5	3,1	1,0-2,5	F3931 030 6
3	8	6,5	3,1	3,0-5,0	F3931 030 8
3	10	6,5	3,1	5,5-7,0	F3931 030 10
3	12	6,5	3,1	7,0-9,0	F3931 030 12
3,2	6	6,5	3,3	1,0-3,0	F3931 032 6
3,2	10	6,5	3,3	5,0-7,0	F3931 032 10
3,2	16	6,5	3,3	9,5-13,0	F3931 032 16
3,9	8	8	4,1	2,0-4,0	F3931 039 8
4	10	8	4,1	4,5-6,5	F3931 039 10
4	12	8	4,1	6,0-8,0	F3931 039 12
4	16	8	4,1	10,0-12,0	F3931 039 16
4	18	8	4,1	10,0-15,0	F3931 039 18
4	14	8	4,1	8,0-10,0	F3931 039 14
4,8	8	9,5	5	2,0-4,5	F3931 049 8
4,8	10	9,5	5	4,5-6,0	F3931 049 10
4,8	12	9,5	5	6,0-8,0	F3931 049 12
4,8	14	9,5	5	8,0-10,0	F3931 049 14
4,8	16	9,5	5	10,0-12,0	F3931 049 16
4,8	18	9,5	5	12,0-14,0	F3931 049 18
4,8	20	9,5	5	14,0-16,0	F3931 049 20
5	8	9,5	5,2	1,5-3,0	F3931 050 8
5	10	9,5	5,2	3,0-5,0	F3931 050 10
5	12	9,5	5,2	5,0-7,0	F3931 050 12
5	16	9,5	5,2	9,0-11,0	F3931 050 16